

SL450 NON-ELECTRIC WATER SOFTENER

EAN	5027639900117
Product code	900117
People	Up to 11
Height	573mm
Depth	503mm
Depth (With Connectors)	580mm
Width	330mm
Approximate regeneration time	24 Minutes
Resin volume	9 Litre (Ultra Fine)
Salt used per regeneration	660gm
Water used per regeneration	24 Litre
Inlet & Outlet	3/4" BSP
Drain & Overflow	1/2"
Includes	2 x Hi-Flow 22mm Hoses
Hi-Flo option	Yes
Power Source	None (Water Pressure)
Installation Orientation	Rear Only
Maximum Ambient Temperature	40°C
Maximum / Minimum Working Pressure	6 bar Max / 1 bar Minimum
Maximum Soft Water (at 200ppm)	2250 Litres
Maximum Soft Water (at 300ppm)	1500 Litres
What salt to use	Granular or Tablet
Warranty	5 Years parts 2 Years Labour*



Simple
'Click-Connect'
Installation

*** IMPORTANT:** To qualify for warranty the softener must be registered and installed in accordance with the Manufacturers installation instructions. Warranty does not cover incorrect installation or setting up of the softener, site damage or resin contamination.

TECHNICAL HELPLINE 01785 811636